

## Power supply unit (CC, DC) dimmable - BASIC, DIM, Multi CC, IE-25D



Image similar

### Prices

<b>List price (VAT included)</b>	64.95 EUR per 1
<b>Minimum order quantity</b>	1
<b>Order step</b>	1

### Information

<b>Order number</b>	862191
<b>EAN</b>	4042943167156

### Description

- Can be dimmed using Dali1/Dali2
- Can be dimmed using 230 V push button [on/off, brightness]
- Intelli-Push function [shortcut synchronises all connected power supply units when needed]
- Current range adjustable using DIP switch
- Can be operated without actuation /dimming
- Dimming range 1-100 %
- Flicker-free
- Short circuit/overload protection, overheating protection

A must-have for every electrician: The MULTI-CURRENT DALI power supply units are all-purpose tools for universal use.

They can be actuated via DALI1 or DALI2 (fully forwards and backwards compatible) or via Intelli-Push. The MULTI-CURRENT power supply units do not require any additional control components and are controlled via cost-effective, 230 V standard push-buttons. With the new Intelli-Push function, you will still have a ground-breaking synchronisation option if one of the connected power supply units is no longer in sync with the others.

In addition, the MULTI-CURRENT power supply units can be operated without actuation or dimming as a reliable and universal power supply. With a total of five models, the new DALI

### Features

<b>RRP incl. VAT</b>	64.95 EUR
<b>Housing Material</b>	Plastic
<b>Housing Color</b>	Black
<b>Operating Mode</b>	Constant current
<b>Frequency</b>	50 / 60 Hz
<b>Inrush Current max.</b>	30 A / 100 µs
<b>Capacitive Load</b>	205.6 nF
<b>Power Factor</b>	0.97
<b>Number of Circuit Breaker B10A max.</b>	23
<b>Number of Circuit Breaker B16A max.</b>	37
<b>Number of Circuit Breaker C10A max.</b>	46
<b>Number of Circuit Breaker C16A max.</b>	74
<b>Connection Type</b>	Clamp
<b>Product weight</b>	118 g
<b>Working Temperature</b>	-20 to 50 °C
<b>Storage Temperature</b>	-20 to 70 °C
<b>Mounting Location</b>	Inside
<b>Rated Input Voltage</b>	220-240 V/AC
<b>Output Voltage</b>	20-60 V/DC
<b>Output Current Selectable in mA</b>	700 mA
<b>Output Current Selectable in mA</b>	600 mA
<b>Output Current Selectable in mA</b>	550 mA
<b>Output Current</b>	

series covers a CC current range of 180 to 1,600 mA and has an output of 4 to 75 W.

- 260 mA/5.0-15.5 W/20-60 V
- 350 mA/7.0-20.0 W/20-60 V
- 400 mA/8.0-24.0 W/20-60 V
- 450 mA/9.0-25.0 W/20-55 V
- 500 mA/10.0-25.0 W/20-50 V
- 550 mA/11.0-25.0 W/20-45 V
- 600 mA/12.0-25.0 W/20-42 V
- 700 mA/14.0-25.0 W/20-36 V

<b>Selectable in mA</b>	500 mA
<b>Output Current</b>	450 mA
<b>Selectable in mA</b>	400 mA
<b>Output Current</b>	350 mA
<b>Selectable in mA</b>	260 mA
<b>Output Current</b>	260 mA
<b>Power</b>	5.0-25.0 W
<b>Control</b>	Intelli Push-Dim
<b>Control</b>	DALI 2.0 / DT6
<b>Dimmable</b>	Yes
<b>Number of Channels</b>	1
<b>Protection Class</b>	Protection class II /protective insulation
<b>Length</b>	119 mm
<b>Width</b>	52 mm
<b>Height</b>	24 mm
<b>IP Protection Class</b>	IP 20
<b>Functions</b>	Overtemperature protection
<b>Functions</b>	Overloading protection
<b>Functions</b>	Protective extra-low voltage
<b>Functions</b>	Furniture installation
<b>Functions</b>	Short-circuit proof
<b>Functions</b>	Lamp control gear 110

