

## Power supply unit (CC, DC) dimmable - BASIC, DIM, CC, D35020UF/20 W



Image similar

### Prices

<b>List price</b> (VAT included)	39.95 EUR per 1
<b>Minimum order quantity</b>	1
<b>Order step</b>	1

### Information

<b>Order number</b>	862204
<b>EAN</b>	4042943167729

### Description

Can be dimmed using leading-edge/trailing-edge phase dimmers Flicker-free Short-circuit-proof, overload protection, overheating protection

### Features

<b>RRP incl. VAT</b>	39.95 EUR
<b>Housing Material</b>	Plastic
<b>Housing Color</b>	Black
<b>Operating Mode</b>	Constant current
<b>Frequency</b>	50 / 60 Hz
<b>Inrush Current max.</b>	15 A / 300 µs
<b>Capacitive Load</b>	30.58 nF
<b>Power Factor</b>	0.97
<b>Number of Circuit Breaker B10A max.</b>	11
<b>Number of Circuit Breaker B16A max.</b>	18
<b>Number of Circuit Breaker C10A max.</b>	24
<b>Number of Circuit Breaker C16A max.</b>	39
<b>Connection Type</b>	Clamp
<b>Product weight</b>	113 g
<b>Working Temperature</b>	-20 to 45 °C
<b>Storage Temperature</b>	-20 to 70 °C
<b>Mounting Location</b>	Inside
<b>Life Time</b>	30000 h
<b>Rated Input Voltage</b>	220-240 V/AC
<b>Output Voltage</b>	28-57 V/DC
<b>Output Current in mA</b>	350 mA
<b>Power</b>	9.8-20.0 W
<b>Control Dimmable</b>	Trailing-edge dimmer Yes

<b>Number of Channels</b>	1
<b>Protection Class</b>	Protection class II /protective insulation
<b>Length</b>	127 mm
<b>Width</b>	44 mm
<b>Height</b>	28 mm
<b>IP Protection Class</b>	IP 20
<b>Functions</b>	Overtemperature protection
<b>Functions</b>	Overloading protection
<b>Functions</b>	Protective extra-low voltage
<b>Functions</b>	Furniture installation
<b>Functions</b>	Lamp control gear 110
<b>Functions</b>	Short-circuit proof

