

Power supply unit (CC, DC) dimmable - BASIC, DIM, Multi CC, IE-12D



Image similar

Prices

List price (VAT included)	59.95 EUR per 1
Minimum order quantity	1
Order step	1

Information

Order number	862190
EAN	4042943167149

Description

- Can be dimmed using Dali1/Dali2
- Can be dimmed using 230 V push button [on/off, brightness]
- Intelli-Push function [shortcut synchronises all connected power supply units when needed]
- Current range adjustable using DIP switch
- Can be operated without actuation /dimming
- Dimming range 1-100 %
- Flicker-free
- Short circuit/overload protection, overheating protection

A must-have for every electrician: The MULTI-CURRENT DALI power supply units are all-purpose tools for universal use.

They can be actuated via DALI1 or DALI2 (fully forwards and backwards compatible) or via Intelli-Push. The MULTI-CURRENT power supply units do not require any additional control components and are controlled via cost-effective, 230 V standard push-buttons. With the new Intelli-Push function, you will still have a ground-breaking synchronisation option if one of the connected power supply units is no longer in sync with the others.

In addition, the MULTI-CURRENT power supply units can be operated without actuation or dimming as a reliable and universal power supply. With a total of five models, the new DALI

Features

RRP incl. VAT	59.95 EUR
Housing Material	Plastic
Housing Color	Black
Operating Mode	Constant current
Frequency	50 / 60 Hz
Inrush Current max.	30 A / 100 µs
Capacitive Load	195.42 nF
Power Factor	0.95
Number of Circuit Breaker B10A max.	23
Number of Circuit Breaker B16A max.	37
Number of Circuit Breaker C10A max.	46
Number of Circuit Breaker C16A max.	74
Connection Type	Clamp
Product weight	99 g
Working Temperature	-20 to 50 °C
Storage Temperature	-20 to 70 °C
Mounting Location	Inside
Rated Input Voltage	220-240 V/AC
Output Voltage	15-52 V/DC
Output Current Selectable in mA	500 mA
Output Current Selectable in mA	450 mA
Output Current Selectable in mA	400 mA
Output Current	

series covers a CC current range of 180 to 1,600 mA and has an output of 4 to 75 W.

- 180 mA/3.2-9.8 W/18-54 V
- 230 mA/4.0-12.0 W/18-52 V
- 260 mA/4.0-12.0 W/15-46 V
- 300 mA/4.5-12.0 W/15-42 V
- 350 mA/5.2-12.0 W/15-34 V
- 400 mA/6.0-12.0 W/15-30 V
- 450 mA/6.8-12.0 W/15-27 V
- 500 mA/7.5-12.0 W/15-24 V

Selectable in mA	350 mA
Output Current	
Selectable in mA	300 mA
Output Current	
Selectable in mA	260 mA
Output Current	
Selectable in mA	230 mA
Output Current	
Selectable in mA	180 mA
Power	3.2-12.0 W
Control	Intelli Push-Dim
Control	DALI 2.0 / DT6
Dimmable	Yes
Number of Channels	1
Protection Class	Protection class II /protective insulation
Length	119 mm
Width	52 mm
Height	24 mm
IP Protection Class	IP 20
Functions	Overtemperature protection
Functions	Overloading protection
Functions	Protective extra-low voltage
Functions	Furniture installation
Functions	Short-circuit proof
Functions	Lamp control gear 110

