



<b>Housing Material</b>	Copper
<b>Housing Color</b>	White
<b>Material of Lens</b>	Silicone
<b>Protection Class</b>	Protection class III/safety extra-low voltage
<b>Operating Mode</b>	Constant voltage
<b>Rated Input 1m</b>	15 W
<b>Rated Power Consumption Standby</b>	0.5 W
<b>Rated Input Voltage</b>	24 V/DC
<b>Power Supply Unit incl.</b>	No
<b>Connection Cable Primary</b>	Yes
<b>Primary Connection</b>	With free strand / conductor ends
<b>Primary Cable Length</b>	1 m
<b>Connection Cable Secondary</b>	Yes
<b>Secondary Connection</b>	Open cables
<b>Secondary Cable Length</b>	1 m
<b>Dimmable</b>	Yes
<b>Control</b>	Dimmable via optional controller
<b>Number of Channels</b>	1
<b>Light Source</b>	LED, Light source not changeable
<b>Lightcolor</b>	Warm white (WW)
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	90
<b>Rated Angle of Reflection</b>	180 Degree
<b>Distribution Characteristic 120°</b>	NDLS
<b>Luminous Flux 1m</b>	1500 lm
<b>Luminous Efficiency 1m</b>	100 lm/W
<b>LED/Meter</b>	480
<b>Segment Length</b>	50 mm
<b>Segment LED Quantity</b>	24
<b>LED Distance</b>	2.08 mm

<b>Bending Radius min.</b>	50 mm
<b>Total Length to be Operated max.</b>	5 m
<b>Length</b>	5000 mm
<b>Width</b>	10 mm
<b>Height</b>	2 mm
<b>Width Hose</b>	14 mm
<b>Height Hose</b>	5 mm
<b>Length end cap</b>	10 mm
<b>Width end cap</b>	15 mm
<b>Height end cap</b>	6 mm
<b>Product weight</b>	449 g
<b>Working Temperature</b>	-15 to 50 °C
<b>Storage Temperature</b>	-10 to 60 °C
<b>IP Protection Class</b>	IP 67
<b>Type of IP Protection</b>	Silicone
<b>Life Time L70 / B50</b>	30000 h
<b>Switching Cycles</b>	100000
<b>Power Consumption EEI</b>	15 kWh/1000h F