



Housing Material	Copper
Housing Color	White
Material of Lens	Silicone
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input 1m	15 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Primary	Yes
Primary Connection	With free strand / conductor ends
Primary Cable Length	1 m
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	1 m
Dimmable	Yes
Control	Dimmable via optional controller
Number of Channels	1
Light Source	LED, Light source not changeable
Lightcolor	Neutral white
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Angle of Reflection	180 Degree
Distribution Characteristic 120°	NDLS
Luminous Flux 1m	1650 lm
Luminous Efficiency 1m	110 lm/W
LED/Meter	480
Segment Length	50 mm
Segment LED Quantity	24
LED Distance	2.08 mm

Bending Radius min.	50 mm
Total Length to be Operated max.	5 m
Length	5000 mm
Width	10 mm
Height	2 mm
Width Hose	14 mm
Height Hose	5 mm
Length end cap	10 mm
Width end cap	15 mm
Height end cap	6 mm
Product weight	438 g
Working Temperature	-15 to 50 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 67
Type of IP Protection	Silicone
Life Time L70 / B50	30000 h
Switching Cycles	100000
Power Consumption EEI	15 kWh/1000h F