




QUALITYFLEX COB-Sauna LED flex lighting, 5 m, CRI > 90, 10 W/m,

IP67

Article no. 15666027

Light.
For Generations.



Tender

LED flex lighting, 5 m, CRI > 90, 10 W/m, IP67, white, 2.700K, CRI > 90. LED flex lighting Length: 5000.0 mm Lamp power per meter: 10.0 W/m, Luminous flux per meter: 840.0 lm/m, Degree of protection: IP67, Protection class: III, Voltage: 24V DC, Beam angle: 120.0 °, 480 LEDs per meter, Chip distance (Short Pitch) : 2,08mm. For individual application, the LED flex board can be used all 50 mm be cut back. If the LED flex board is shortened, the IP protection must be restored by the customer. The maximum system length of 5.000mm must not be exceeded with one feed-in.

Product Benefits

- Mounting by retaining clips directly on the substrate.
- High color rendering with CRI > 90.
- Chip-on-board LED assembly for homogeneous light pattern.
- Continuous light emission over the length of the board.
- Ideal for use at higher ambient temperature, steam bath / sauna.
- Color temperature 2700 Kelvin or 3000 Kelvin.
- Suitable for indoor use only.
- Pitch of 50 millimeters.
- Light color: monochrome white.
- Dimmable with appropriate accessories.

QUALITYFLEX COB-Sauna LED flex lighting, 5 m, CRI > 90, 10 W/m, IP67

Article no. 15666027

Light.
For Generations.

Article data	
Article no.	15666027
GTIN	4251433957867
Series name	QUALITYFLEX COB-Sauna
Short description	LED flex lighting, 5 m, CRI > 90, 10 W/m, IP67
Colour	White
Length	5,000 mm
Width	12 mm
Height	5.5 mm
Scope of delivery	incl. 3 pieces „End cap IP65” incl. 15 pieces of mounting clips and 30 pieces of screws incl. 1 piece connection cable 30cm long connection cable, red = „+” black = „-” Back adhesive strip „TESA 4965”
Weight	0.472 kg
Length of the connection line	300 mm
Conformance	CE, UKCA

Lighting technology	
Colour temperature	2.700 K
Light colour	White
Luminous flux per meter	840 lm/m
System efficiency	84 lm/W
McAdam-Step	McAdam-Step 5
Colour rendering	CRI > 90
Beam angle	120°
Adjustable color temperature	No

Operating technology of the luminaire	
System output	50 W
Lamp power per meter	10 W/m
Voltage type	DC
DC nominal voltage max	24 V
Lamp	LED
Protection class	III
Degree of protection	IP67
Ambient temperature	-25 °C up to +105 °C
Dimmable	Yes
Wire number	2
Control	Depending on driver
Length of the connection line	300 mm
Cable assignment	red = + pole black = - pole
Design of the connecting cable	one-sided
Bulb change possible	No
Rated life time L70/B50 at 25 °C	50,000 h
Rated life time L80/B10 at 25 °C	36.000 h
Energy efficiency class	F

QUALITYFLEX COB-Sauna LED flex lighting, 5 m, CRI > 90, 10 W/m, IP67

Article no. 15666027

Light.
For Generations.

Operating technology of QualityFlex	
Power per meter	10 W/m
Short Pitch	2.08 mm
Number of lamps per meter	480 Qty
Length of individual sections	50 mm
Smallest bend radius	40 mm
Length	5,000 mm
Maximum module length	5,000 mm
Circuit type	Parallel conduction
LED Type	COB-LED

Packing data	
Gross weight	0.522 kg
Length of packaging	270 mm
Packaging width	280 mm
Packaging height	50 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

Compatible Driver						
Article no.	Power min	Power	Control	Length	Width	Height
17206000	1 W	20 W	1-10 V	146 mm	55 mm	19 mm
17207000	1 W	30 W	on/off	160 mm	50 mm	22 mm
17214000	1 W	7.2 W	on/off	68 mm	35 mm	21 mm
17223000	1 W	75 W	on/off	185 mm	60 mm	31 mm
17224000	1 W	100 W	on/off	199 mm	63 mm	36 mm
17225000	1 W	150 W	on/off	219 mm	63 mm	36 mm
17226000	1 W	240 W	on/off	244 mm	71 mm	38 mm
17227000	1 W	320 W	on/off	252 mm	90 mm	44 mm
17228000	1 W	480 W	on/off	262 mm	125 mm	44 mm
17230000	5 W	30 W	Trailing-edge phase	145 mm	50 mm	22 mm
17231000	12 W	75 W	Trailing-edge phase	185 mm	60 mm	31 mm
17232000	12 W	120 W	Trailing-edge phase	223 mm	64 mm	32 mm
17240000	1 W	20 W	on/off	150 mm	40 mm	30 mm
17241000	1 W	40 W	on/off	210 mm	40 mm	30 mm
17242000	1 W	60 W	on/off	250 mm	40 mm	30 mm
17243000	1 W	120 W	on/off	300 mm	40 mm	30 mm
17244000	1 W	150 W	on/off	310 mm	40 mm	30 mm
17250000	1 W	45 W	DALI-2	187 mm	45 mm	31 mm
17251000	1 W	80 W	DALI-2	290 mm	45 mm	31 mm
17252000	1 W	150 W	DALI-2	290 mm	45 mm	31 mm
17260000	1 W	150 W	on/off	105 mm	90 mm	59 mm

QUALITYFLEX COB-Sauna LED flex lighting, 5 m, CRI > 90, 10 W/m, IP67

Article no. 15666027

Light.
For Generations.

Compatible Conroller						
Article no.	Power min	Power	Control	Length	Width	Hight
17502000	1 W	120 W	DALI	183 mm	33 mm	23 mm
18151000	1 W	240 W	KNX	170 mm	59 mm	30 mm
18152000	1 W	240 W	DALI-DT6	170 mm	59 mm	30 mm
18153000	1 W	240 W	DMX	170 mm	59 mm	30 mm
18154000	1 W	240 W	1-10 V	170 mm	59 mm	30 mm
18161000	1 W	240 W	KNX	72 mm	90 mm	70 mm
18162000	1 W	240 W	DALI-DT6	54 mm	110 mm	66 mm
18164000	1 W	240 W	1-10 V	54 mm	110 mm	66 mm
17528000	1 W	240 W	Wireless technology control			
17511000	1 W	240 W	Wireless technology control	145 mm	46.5 mm	16 mm
18157000	1 W	240 W	ZigBee	145 mm	46.5 mm	16 mm
18192000	1 W	240 W	Wireless technology control	160 mm	45 mm	18 mm

Compatible Profiles						